




**VOLTAGE OUTPUT DIGITALLY CORRECTED PRESSURE TRANSDUCER**

**BME-88-1000 Series**

- Ideal for Static Pressure Measurements
- Robust Construction
- High Accuracy
- Digitally Corrected
- Silicon on Silicon Integrated Sensor **VIS®**
- Intrinsically Safe Applications Available (i.e. IS-BME-88-1000)



The BME-88-1000 offers a high accuracy voltage output with a total error band of  $\pm 0.25\%$  FSO across the ultra-wide temperature range of  $-40^{\circ}\text{F}$  to  $+284^{\circ}\text{F}$  ( $-40^{\circ}\text{C}$  to  $+140^{\circ}\text{C}$ ). Designed to measure liquid or gas pressure (with its all-welded, hermetic stainless steel construction), the transducer is ideal for road test, flight test and industrial sensing applications.



INPUT	Pressure Range (Note 1)	15	30	50	100	200	750	1000	2000	5000 PSI	
	Operational Mode	Absolute									
	Over Pressure	2 Times Rated Pressure to a Maximum of 5000 PSI (350 BAR)									
	Burst Pressure	5 Times Rated Pressure to a Maximum of 5000 PSI (350 BAR)									
	Pressure Media	Any Media Compatible With 316 SS Stainless Steel									
	Rated Electrical Excitation	8 - 30 VDC (8-24 VDC For IS)									
	Maximum Electrical Current	3.5 mA (Max.)									
OUTPUT	Output Impedance	250 Ohms (Max.)									
	Full Scale Output (Net)	4.0 VDC $\pm 0.025$ VDC									
	Total Error Band (Excluding End Points)	$\pm 0.25\%$ FSO (Max.) (Combined Non-Linearity, Hysteresis, Repeatability and All Thermal Effects Included)									
	Residual Unbalance	0.5 VDC $\pm 0.025$ VDC									
	Insulation Resistance	100 Megohm Min. @ 50 VDC									
ENVIRONMENTAL	Operating Temperature Range	$-40^{\circ}\text{F}$ to $+284^{\circ}\text{F}$ ( $-40^{\circ}\text{C}$ to $+140^{\circ}\text{C}$ )									
	Compensated Temperature Range	$-40^{\circ}\text{F}$ to $+284^{\circ}\text{F}$ ( $-40^{\circ}\text{C}$ to $+140^{\circ}\text{C}$ )									
	Humidity	100% Relative Humidity									
PHYSICAL	Electrical Connection	PTIH-10-6P Connector or Equivalent									
	Weight	100 Grams (Nom)									
	Pressure Sensing Principle	Fully Active Four Arm Wheatstone Bridge Dielectrically Isolated Silicon on Silicon									
	Mounting Torque	75 Inch-Pounds (Max.) (8.5 Nm)									

Note 1: Custom pressure ranges, accuracies and mechanical configurations available. Dimensions are in inches. Dimensions in parenthesis are in millimeters. All dimensions nominal. (J) Continuous development and refinement of our products may result in specification changes without notice. Copyright © 2020 Kulite Semiconductor Products, Inc. All Rights Reserved. Kulite miniature pressure transducers are intended for use in test and research and development programs and are not necessarily designed to be used in production applications. For products designed to be used in production programs, please consult the factory.